

GreaseMax is designed to operate at an average temperature of 25°C. The discharge rate and operating period of **GreaseMax** will be different if the average operating temperature varies from 25°C. The following table gives details.

	Type 1 White (1 mth)		Type 3 Blue (3 mth)		Type 6 Red (6 mth)		Type 12 Grey (12 mth)	
Average temp.	Life in months	Grease supply / day grams	Life in months	Grease supply / day grams	Life in months	Grease supply / day grams	Life in months	Grease supply / day grams
65°C	0.15	24.0	0.5	8.0	1	3.6	2	1.8
55°C	0.3	12.0	1	3.6	2	1.8	4	0.9
45°C	0.5	7.3	1.5	2.3	3	1.2	6	0.6
35°C	0.7	5.2	2.5	1.5	4.5	0.8	9	0.4
25°C	1	3.6	3	1.2	6	0.6	12	0.3
15°C	1.5	2.3	4.5	0.8	9	0.4	18	0.2
5°C	2	1.8	6	0.6	12	0.26	24	0.13
-5°C	4	0.9	12	0.3	24	0.15	48	0.08
-15°C	6	0.6	18	0.2	36	0.1		
-25°C	9	0.4	27	0.13				

Note: The average temperature is the average operational temperature of the **GreaseMax** unit. This may be different to the average environmental temperature.